



# nses

K51300.03.TR.WH-BK.45.ST.9.40.PC




## GENERAL DETAILS

| | |
|---|---|
| INSTALLATION | Trimless |
| FINISHES ALUMINIUM | Black-White |
| LIGHT DIRECTION | Fixed |
| BEAM ANGLE | 45º |
| INT/EXT IP DEGREE | IP20 |
| MATERIAL | Aluminum |
| IK DEGREE | IK 6 |
| UTILIZATION | Indoor |
| WARRANTY | 5 years |

## ELECTRICAL DETAILS

| | |
|---|---|
| LAMP | LED |
| POWER | 20 W |
| COLOUR TEMPERATURE | 4000K |
| LUMINOUS FLUX | 1630 Lm |
| EFFICACY DIMMING | 78 Lm/W |
| DIMABLE | PHASE CUT |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI>90 |
| VOLTAGE | 220-240 V |
| CURRENT INTENSITY | 600 mA |
| LIFE TIME | 50.000 h |

## GENERAL DIMENSIONS

| | |
|---|---|
| DIMENSIONS | .03 (270x35mm) |
| CUT OUT | 275x70 mm |
| HEIGHT | h 56.5 mm |
| DIMENSIONES DE EMBALAJE | 325 × 80 × 85 mm |
| PESO NETO | 86 |

*Please might expect a max.15% figure reduction in finishes other than white