



nses
K51300.SR

GENERAL DETAILS

INSTALLATION	Surface
FINISHES ALUMINIUM	Black-Black, Black-White
LIGHT DIRECTION	Fixed
BEAM ANGLE	15°, 30°, 45°
INT/EXT IP DEGREE	IP20
MATERIAL	Aluminum
IK DEGREE	IK 6
UTILIZATION	Indoor
WARRANTY	3 years

ELECTRICAL DETAILS

LAMP	LED
POWER	10W, 20 W
COLOUR TEMPERATURE	2700K, 3000K, 4000K
LUMINOUS FLUX	835 Lm, 875 Lm, 915 Lm, 1430 Lm, 1530 Lm, 1630 Lm
EFFICACY DIMMING	68 Lm/W, 70 Lm/W, 73 Lm/W, 76 Lm/W, 78 Lm/W
DIMABLE	No Dim
DRIVER	Integrated
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI>90
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	600 mA, 700 mA
LIFE TIME	35.000 h

GENERAL DIMENSIONS

DIMENSIONS	137×35 mm, 270×35 mm
HEIGHT	h 80 mm
DIMENSIONES DE EMBALAJE	N/A

*Please might expect a max.15% figure reduction in finishes other than white