


n ses
K51300.02.SR.BK-BK.15.ST.9.40



GENERAL DETAILS

| | |
|--------------------|-------------|
| INSTALLATION | Surface |
| FINISHES ALUMINIUM | Black-Black |
| LIGHT DIRECTION | Fixed |
| BEAM ANGLE | 15° |
| INT/EXT IP DEGREE | IP20 |
| MATERIAL | Aluminum |
| IK DEGREE | IK 6 |
| UTILIZATION | Indoor |
| WARRANTY | 3 years |

ELECTRICAL DETAILS

| | |
|------------------------|------------|
| LAMP | LED |
| POWER | 20 W |
| COLOUR TEMPERATURE | 4000K |
| LUMINOUS FLUX | 1630 Lm |
| EFFICACY DIMMING | 78 Lm/W |
| DIMABLE | No Dim |
| DRIVER | Integrated |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI>90 |
| VOLTAGE | 220-240 V |
| FRECUENCIA | 50-60 Hz |
| CURRENT INTENSITY | 600 mA |
| LIFE TIME | 35.000 h |

GENERAL DIMENSIONS

| | |
|-------------------------|-------------------|
| DIMENSIONS | 270×35 mm |
| HEIGHT | h 80 mm |
| DIMENSIONES DE EMBALAJE | 290 × 150 × 45 mm |

*Please might expect a max.15% figure reduction in finishes other than white