



## GENERAL DETAILS

|                    |                     |
|--------------------|---------------------|
| INSTALLATION       | recessed with frame |
| FINISHES ALUMINIUM | White-White         |
| LIGHT DIRECTION    | Orientable          |
| TILTING DEGREES    | 30°                 |
| ROTATION DEGREES   | 350°                |
| BEAM ANGLE         | 20°                 |
| INT/EXT IP DEGREE  | IP 23               |
| MATERIAL           | Aluminum            |
| IK DEGREE          | IK05                |
| UTILIZATION        | Indoor              |
| WARRANTY           | 5 years             |

## ELECTRICAL DETAILS

|                        |            |
|------------------------|------------|
| LAMP                   | LED        |
| POWER                  | 10W        |
| COLOUR TEMPERATURE     | 3000K      |
| LUMINOUS FLUX          | 880 Lm     |
| EFFICACY DIMMING       | 78-82 lm/W |
| DIMABLE                | DALI       |
| DRIVER                 | Remote     |
| CLASS PROTECTION       | II         |
| COLOUR RENDERING INDEX | CRI>90     |
| VOLTAGE                | 220-240 V  |
| FRECUENCIA             | 50-60 Hz   |
| CURRENT INTENSITY      | 300 mA     |
| LIFE TIME              | 50.000 h   |

## GENERAL DIMENSIONS

|                         |                    |
|-------------------------|--------------------|
| DIMENSIONS              | 93×93 mm           |
| CUT OUT                 | Ø 80 mm            |
| HEIGHT                  | h 90 mm            |
| DIMENSIONES DE EMBALAJE | 125 × 110 × 110 mm |
| PESO NETO               | 0.24               |

\*Please might expect a max.15% figure reduction in finishes other than white

**rebecca sq**  
K53271.01.RF.WH-WH.20.ST.9.30.DA

