




rebecca

K53270.01.RF.ALUMN.35.ST.9.30.PU



GENERAL DETAILS

| | |
|--------------------|---------------------|
| INSTALLATION | recessed with frame |
| FINISHES ALUMINIUM | Aluminum |
| LIGHT DIRECTION | Orientable |
| TILTING DEGREES | 30° |
| ROTATION DEGREES | 350° |
| BEAM ANGLE | 35° |
| INT/EXT IP DEGREE | IP 23 |
| MATERIAL | Aluminum |
| IK DEGREE | IK05 |
| UTILIZATION | Indoor |
| WARRANTY | 5 years |

ELECTRICAL DETAILS

| | |
|------------------------|------------|
| LAMP | LED |
| POWER | 10W |
| COLOUR TEMPERATURE | 3000K |
| LUMINOUS FLUX | 880 Lm |
| EFFICACY DIMMING | 78-82 lm/W |
| DIMABLE | Push |
| DRIVER | Remote |
| CLASS PROTECTION | II |
| COLOUR RENDERING INDEX | CRI>90 |
| VOLTAGE | 220-240 V |
| CURRENT INTENSITY | 300 mA |
| LIFE TIME | 50.000 h |

GENERAL DIMENSIONS

| | |
|-------------------------|--------------------|
| DIMENSIONS | Ø 93 mm |
| CUT OUT | Ø 80 mm |
| HEIGHT | h 90 mm |
| DIMENSIONES DE EMBALAJE | 125 × 110 × 110 mm |
| PESO NETO | 0.22 |

*Please might expect a max.15% figure reduction in finishes other than white