



storm pro k-select

K60011.SR

GENERAL DETAILS

INSTALLATION	Surface
FINISHES ALUMINIUM	Black-Black
LIGHT DIRECTION	Fixed
BEAM ANGLE	120°
INT/EXT IP DEGREE	IP 66
MATERIAL	Aluminum
IK DEGREE	IK08
UTILIZATION	Outdoor
WARRANTY	3 years

ELECTRICAL DETAILS

LAMP	LED
POWER	20 W, 30 W, 50 W, 100 W
COLOUR TEMPERATURE	3CCT 3000K-4000K-6000K
LUMINOUS FLUX	1850-1900-1950 Lm, 2900-2950-3000 Lm, 4930-4950-5000 Lm, 9900-9950-10000 Lm
EFFICACY DIMMING	93-95-98 Lm/W, 97-98-100 Lm/W, 99-99-100 Lm/W
DRIVER	Integrated
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	200-277 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	75 mA, 120 mA, 200 mA, 350 mA
LIFE TIME	35.000 h

GENERAL DIMENSIONS

DIMENSIONS	182×47 mm, 242×51 mm, 282×52 mm, 337×52 mm
HEIGHT	h 122 mm, h 169 mm, h 204 mm, h 269 mm
DIMENSIONES DE EMBALAJE	N/A

*Please might expect a max.15% figure reduction in finishes other than white