

versus litl

K51103.RF

GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	Black-White, Gold Cava-Negro
LIGHT DIRECTION	Fixed
BEAM ANGLE	30º
INT/EXT IP DEGREE	IP 32
MATERIAL	Aluminum
IK DEGREE	IK05
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	3 W
COLOUR TEMPERATURE	2700K, 3000K, 4000K
LUMINOUS FLUX	90 Lm, 130 Lm, 133 Lm
EFFICACY DIMMING	36 Lm/W, 38 Lm/W, 44 Lm/W
DIMABLE	1.10v, DALI, No Dim, PHASE CUT, Push
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
CURRENT INTENSITY	600 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	Ø 44 mm
CUT OUT	Ø 40 mm
HEIGHT	h 40 mm
DIMENSIONES DE EMBALAJE	82 × 52 × 78 mm
PESO NETO	00.86

*Please might expect a max.15% figure reduction in finishes other than white