


versus

K51100.01.RF.BK-GL.38.ST.8.30.PU



GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	Black-Gold
LIGHT DIRECTION	Fixed
BEAM ANGLE	38º
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminum
IK DEGREE	IK03
UTILIZATION	Indoor
WARRANTY	5 years

ELECTRICAL DETAILS

LAMP	LED
POWER	5 W
COLOUR TEMPERATURE	3000K
LUMINOUS FLUX	400 lm
EFFICACY DIMMING	74 Lm/W
DIMABLE	Push
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
CURRENT INTENSITY	120 mA
LIFE TIME	50.000 h

GENERAL DIMENSIONS

DIMENSIONS	Ø 60 mm
CUT OUT	Ø 55 mm
HEIGHT	h 70 mm
DIMENSIONES DE EMBALAJE	95 × 135 × 85 mm
PESO NETO	0.17

*Please might expect a max.15% figure reduction in finishes other than white

Partida Madrigueres Sud 63A, Naves1-4, 03700 Dénia · Alicante (Spain) | Tel. 0034 96 575 3083 · info@kohl-lighting.com · www. kohl-lighting.com