



**versus**  
K51100.03.RF.WH-WH.38.ST.8.30.D1



## GENERAL DETAILS

INSTALLATION	recessed with frame
FINISHES ALUMINIUM	White-White
LIGHT DIRECTION	Fixed
BEAM ANGLE	38°
INT/EXT IP DEGREE	IP 23
MATERIAL	Aluminum
IK DEGREE	IK03
UTILIZATION	Indoor
WARRANTY	3 years

## ELECTRICAL DETAILS

LAMP	LED
POWER	15 W
COLOUR TEMPERATURE	3000K
LUMINOUS FLUX	1275 Lm
EFFICACY DIMMING	91 Lm/W
DIMABLE	1.10v
DRIVER	Remote
CLASS PROTECTION	II
COLOUR RENDERING INDEX	CRI >80
VOLTAGE	220-240 V
FRECUENCIA	50-60 Hz
CURRENT INTENSITY	350 mA
LIFE TIME	50.000 h

## GENERAL DIMENSIONS

DIMENSIONS	Ø 80 mm
CUT OUT	Ø 75 mm
HEIGHT	h 100 mm
DIMENSIONES DE EMBALAJE	115 × 165 × 115 mm
PESO NETO	0.38

\*Please might expect a max.15% figure reduction in finishes other than white